



IPZ-E8233W-I150

33X Starlight IR Network PTZ Dome Camera

Key Features

- زوم اپتیکال تا 33 برابر بزرگ نمای
- IR هوشمند تا 150 متر
- طلق ضد بازتاب نور مادون قرمز
- تثبیت کننده الکترونیکی لرزش تصویر
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- تکنولوژی کنترل دمای هوشمند
- طراحی موثر دفع گرما
- مقاومت در برابر نفوذ آب و گرد و غبار IP66

Specifications

sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS					Motion Detection	Up to 4 areas
Lens	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens					General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Digital Zoom	16					Audio Compression	6.711
Optical Zoom	33					Two-way Audio	Supported
Angle of View (H)	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Suppression	Supported
Angle of View (V)	4.5	69.8	27.9	14.0	7.0	Sampling Rate	8KHZ
Angle of View (O)	148.5	2304.3	921.7	460.9	230.4	Edge Storage	Micro SD, up to 256GB
Angle of View (H)	P76.8° - 2.1°					Network Storage	ANR
Angle of View (V)	38.4° - 1.2°					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS
Angle of View (O)	94.46° - 2.48°					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Shutter	Auto/Manual, shutter time: 1 - 1/100000s					Pan Range	360°
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON) 0Lux with IR					Pan Speed	0.1°/s - 300°/s Preset speed: 200°/s
Iris	F1.5 - F4.0					Tilt Range	-15° - 90° (auto reverse)
Day/Night	IR-cut filter with auto switch (ICR)					Tilt Speed	0.1° - 80°/s Preset speed: 80°/s
Digital noise reduction	2D/3D DNR					Number of Presets	1024
S/N	>55 dB					Patrol	Preset patrol, route patrol, recorded patrol
IR Range	UP to 150m (492ft)					Home Position	Supported
Defog	Digital Defog					Audio I/O	1 Input: impedance 1kΩ±10%; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
WDR	120dB					Alarm I/O	2/1
Video Compression	Ultra 265, H.265, H.264, MJPEG					Power	DC 12V±25%, PoE (PSE Required) Power consumption: 16 - 30W
H.264 code profile	Baseline profile, Main Profile, High Profile					Dimensions (ø x H)	Ø220 x 369mm (Ø8.7" x 14.5")
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps					Weight	3kg (6.6lb)
HLC	Supported					Working Environment	-40°C - 65°C [-40°F - 149°F], Humidity: ≤95% RH (non-condensing)
BLC	Supported					Ingress Protection	IP66
EIS	Supported					Reset Button	Supported
OSD	Up to 8 OSDs						
Privacy Mask	Up to 24 areas						
ROI	Up to 8 areas						

Dimensions

