

IPC-A1A2WH-I200S

2MP 22x Starlight WDR Network IR Bullet Camera



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند تا 200 متر
- کاهنده نویز دیجیتال 3D
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/1.8", 2.0 megapixel, progressive scan, CMOS					Motion Detection	Up to 4 areas
Lens	6.5 - 143mm, AF automatic focusing and motorized zoom lens					Smart Features	Audio detection, Cross line, intrusion, object left, object removed, People Counting, Face Capture
Optical Zoom	22					Privacy Mask	Up to 8 areas
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)	General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
	6.5	78	31.2	15.6	7.8		
Angle of View (H)	143	1716	686.4	343.2	171.6	Audio Compression	G.711
	59° - 3°					Two-way audio	Supported
Angle of View (V)	34.6° - 1.6°					Suppression	Supported
Angle of View (D)	72.6° - 3.6°					Sampling Rate	8KHZ
Adjustment angle	Pan: 0°-360°		Tilt: 0°-90°		Rotate: 0°-360°	Edge Storage	Micro SD, up to 256GB
Shutter	Auto/Manual, 1 - 1/100000s					Network Storage	ANR
Minimum Illumination	Colour: 0.0005Lux (F1.5, AGC ON) 0Lux with IR					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Iris	Auto/Manual, F1.5 - F3.4, DC-Iris					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Day/Night	IR-cut filter with auto switch (ICR)					Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
Digital noise reduction	2D/3D DNR					Alarm I/O	2/1
S/N	>52dB					Serial Port	1 RS485
IR Range	up to 200m (656ft) IR range					Network	1 RJ45 10M/100M Base-TX Ethernet
Defog	Defog Digital					Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
WDR	120dB					Power	AC 24V±25%, PoE (IEEE 802.3at) Power consumption: Max 21W
Video Compression	Ultra 265, H.265, H.264, MJPEG					Dimensions (L x W x H)	396.5 x 137 x 112mm (15.6" x 5.4" x 4.4")
H.264 code profile	Baseline profile, Main Profile, High Profile					Weight	3.7kg (8.2lb)
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps					Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
9:16 Corridor Mode	Supported					Ingress Protection	IP67
ROI	Supported					Reset Button	Supported
HLC	Supported						
BLC	Supported						
OSD	Up to 8 OSDs						

Dimensions

