

IPC-E1A2W-I50

2MP HD IR VF Bullet Network Camera



قابلیت های کلیدی

- OSD قابل تنظیم
- قابلیت شب و روز
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265، H.264، MJPEG
- دارای میکروفون داخلی
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS					White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens					Digital Noise Reduction	2D/3D DNR
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Smart IR	Supported
	2.8	42	168	8.4	4.2	Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Angle of View [H]	108.05°~32.59°					Dewarping	N/A
Angle of View [V]	56.81°~18.36°					HLC	Supported
Angle of View [D]	111.91°~36.53°					BLC	Supported
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°	Rotate: 0° ~ 360°		Audio Compression	G.711
Shutter	Auto/Manual, 1 - 1/100000s					Suppression	Supported
Minimum Illumination	Colour: 0.005Lux (F1.6,AGC ON) 0Lux with IR on					Sampling Rate	8KHZ
Day/Night	IR-cut filter with auto switch (ICR)					Edge Storage	Micro SD, up to 128GB
Digital noise reduction	2D/3D DNR					Network Storage	ANR,NAS(NFS)
S/N	>52dB					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
IR Range	50-80m IR range					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Wavelength	850nm					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
IR On/Off Control	Auto/Manual					Network	10/100M Base-TX Ethernet
Defog	Digital Defog					Built-in Mic	Supported
WDR	120dB					Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
Video Compression	Ultra 265, H.265, H.264, MJPEG					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.5W
H.264 code profile	Baseline profile, Main profile, High profile, MJPEG					Dimensions (L x W x H)	206 x 74 x 74mm (8.1" x 2.9" x 2.9")
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;					Net Weight	0.54kg (1.19lb)
Video Bit Rate	128 Kbps~16 Mbps					Material	metal
9:16 Corridor Mode	Supported					Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
OSD	Up to 4 OSDs					Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Privacy Mask	Up to 4 areas					Surge Protection	6KV
ROI	Up to 8 areas					Ingress Protection	IP67
Motion DetectionSmart	Up to 4 areas					Reset Button	Supported
Smart Features	Tampering detection, Audio detection, Human body detection						

Dimensions

