

IPC-E1F4D-I30 4.0mm

4MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از ROI
- قابلیت روز و شب
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز

Specifications

sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0				
DDRI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	90	36	18	9
Angle of View (H)	78.9°				
Angle of View (V)	39.6°				
Angle of View (D)	97.0°				
Adjustment angle	Pan: 0° ~ 360°	Tilt: 0° ~ 90°	Rotate: 0° ~ 360°		
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	30-50m IR range				
WDR	100dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps; Third Stream: D1 (720*576), Max 20fps				
HLC	Supported				
BLC	Supported				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				
Motion Detection	Up to 4 areas				
Smart Features	intrusion, Human body detection				
Intrusion	Enter and loiter in a pre-defined virtual region				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS				
Compatible Integration Network	ONVIF (Profile S, Profile T), API 10/100M Base-TX Ethernet				
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5W				
Dimensions (L x W x H)	167.3 x 62.9 x 62.7mm [6.6" x 2.5" x 2.5"]				
Weight	0.45kg [0.99lb]				
Working Environment	-30°C ~ 60°C [-22°F ~ 140°F], Humidity: ≤95% RH (non-condensing)				
Ingress Protection	IP67				
Reset Button	Supported				

Dimensions

