

IPC-E1F5D-I30 4.0mm

5MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	60	24	12	6
Angle of View (H)	79.7°				
Angle of View (D)	51.8°				
Adjustment angle	98.0°				
Shutter	Pan: 0° ~ 360°		Tilt: 0° ~ 90°		Rotate: 0° ~ 360°
	Digital noise reduction				
	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON)				
	0Lux with IR on				
Day/Night	2D/3D DNR				
S/N	IR-cut filter with auto switch (ICR)				
IR Range Up	>52dB				
Wavelength	30-50m IR range				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	100dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				
Frame Rate	Main Stream: 5MP (2592*1944), Max 20fps;				
	Sub Stream: 720P (1280*720), Max 20fps				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				
Motion Detection	Up to 4 areas				

Smart Features	Tampering detection, Intrusion Detection, Human body detection
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Protocols	IPv4, IG MP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Network	10/100M Base-TX Ethernet
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 4W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm [6.6" × 2.5" × 2.5"]
Net Weight	0.45kg [0.99lb]
Material	Metal
Working Environment	-30°C ~ 60°C [-22°F ~ 140°F], Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C [-22°F ~ 140°F], Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

Dimensions

