

IPC-E1F5W-I50

5MP Mini IR Fixed Bullet Network Camera



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دارای میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از حالت راهرو 9:16
- IR هوشمند 50 تا 70 متر
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG
- دارای میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS					Dewarping	NA
Minimum Illumination	Support EasyStar: Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on					HLC	Supported
Day/Night	IR-cut filter with auto switch (ICR)					BLC	Supported
Shutter	Auto/Manual, 1 - 1 100000s					Defog	Digital Defog
Adjustment angle	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°					General Function	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication
S/N	>56dB					Smart Features	Audio detection, Cross Line, Intrusion detection (based on human body detection)
WDR	120dB					Audio Compression	G.711
Lens Type	2.8mm @1.6, Fixed-focal					Suppression	Supported
Lens Mount	M12					Sampling Rate	8KHZ
Angle of View (H)	112.9°					Edge Storage	Micro SD, up to 256GB
Angle of View (V)	59.1°					Network Storage	ANR, NAS(NFS)
Angle of View (D)	121.2°					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
	2.8	63.0	25.2	12.6	6.3	User/Host	Up to 32 users. 2 user levels: administrator and common user
IR Range	50-70m IR range					Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Wavelength	850nm					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
IR On/Off Control	Auto/Manual					Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Compression	Ultra 265, H.265, H.264, MJPEG					Built-in Mic	Supported
Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP(2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5.5W
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; 720P (1280*720), Max 30fps;					Power Interface	Ø 5.5mm coaxial power plug
Video Bit Rate	128 Kbps-16 Mbps					Dimensions (L x W x H)	191x 75 x 74mm (7.5" x 3.0" x 2.9")
9:16 Corridor Mode	Supported					Weight	0.40kg (0.88lb)
OSD	Up to 4 OSDs					Material	Metal
Privacy Mask	Up to 4 areas					Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
ROI	Up to 8 areas					Surge Protection	4KV
Motion Detection	Up to 4 areas					Reset Button	N/A
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2					Ingress Protection	Ingress protection: IP67
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser						
Digital noise reduction	2D/3D DNR						
Flip	Normal/Vertical/Horizontal/180°						

Dimensions

