

IPC-E2A5D-I30

5MP VF Vandal-resistant IR Dome Network Camera



قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 30 تا 60 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265، H.264، MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت

Specifications

| | | | | | |
|-------------------------|--|------------|----------------|---------------|-------------------|
| Sensor | 1/2.7", 5.0 megapixel, progressive scan, CMOS | | | | |
| Lens | 2.8 - 12mm, motorized zoom lens | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.8 | 63 | 25.2 | 12.6 | 6.3 |
| Angle of View (H) | 105.3° - 25.4° | | | | |
| | 69.5° - 18.4° | | | | |
| Angle of View (V) | 136.9° - 31.2° | | | | |
| Adjustment angle | Pan: 0° - 360° | | Tilt: 0° - 80° | | Rotate: 0° - 360° |
| Shutter | Auto/Manual, 1 - 1/100000s | | | | |
| Minimum Illumination | Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Digital noise reduction | 2D/3 | | | | |
| IR Range | 30-60m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Defog | Digital Defog | | | | |
| WDR | 100dB | | | | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG | | | | |
| H.264 code profile | Baseline profile, Main Profile | | | | |
| Frame Rate | Main Stream: 5MP (2592*1944), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps | | | | |
| Video Bit Rate | 128 Kbps-16 Mbps | | | | |
| OSD | Up to 4 OSDs | | | | |
| Privacy Mask | Up to 4 areas | | | | |
| ROI | Up to 2 areas | | | | |
| Motion Detection | Up to 4 areas | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |

| | |
|-------------------------|--|
| Smart Features | Tampering detection, Intrusion detection, Human body detection |
| Digital noise reduction | 2D/3D DNR |
| Smart IR | Support |
| Flip | Flip Normal/Vertical/Horizontal/180° |
| Dewarping | NA |
| HLC | Supported |
| BLC | Supported |
| Edge Storage | Micro SD, up to 256 GB |
| Network Storage | ANR |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API |
| Web Browser | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ |
| Network | 1 RJ45 10M/100M Base-TX Ethernet |
| Certifications | CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15 |
| Power | DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.7W |
| Dimensions (Ø x H) | Ø148 x 111.3mm (Ø5.8" x 4.4") |
| Net Weight | 0.92kg (2.0lb) |
| Material | Metal + Plastic |
| Working Environment | -40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Surge Protection | 6KV |
| Ingress Protection | IP67 |
| Vandal Resistant | IK10 |
| Reset Button | Supported |

Dimensions

