

# IPC-E2A5W-I40S

5MP HD IR VF Dome Network Camera



## قابلیت های کلیدی

- پشتیبانی از حالت راهرو 9:16
- IR هوشمند 40 تا 70 متر
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG
- دارای میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت

## Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
DORI Distance	12	270.0	108.0	54.0	27.0
Angle of View (H)	108.79°~ 33.23°				
Angle of View (V)	56.90°~ 18.33°				
Angle of View (D)	112.56°~37.46°				
Adjustment angle	Pan: 3° ~ 360°		Tilt: 0° ~ 70°		Rotate: 3° ~ 360°
Shutter	Auto/Manual, 1 - 1/100000s				
Min. Illumination	Colour: 0.00 3Lux (F1.6, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>56dB				
IR Range	40-70m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF(352*288), Max 30fps;				
Video Bit Rate	128 Kbps-16 Mbps				
9:16 Corridor Mode	Supported				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				

Smart Features	Audio detection, Cross Line, Intrusion detection (based on Human body detection)
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS, SNMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Audio I/O	N/A
Alarm I/O	N/A
Network	10/100M Base-TX Ethernet
Built-in Mic	Supported
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.5W
Dimensions (L x W x H)	Φ128mmx100mm (Ø5.0" x 3.9")
Net Weight	0.65kg (1.43lb)
Material	Metal + Plastic
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported

## Dimensions

