

IPZ-P6222WH-I150S

2MP 22X Lighthunter IR Network PTZ Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- تکنولوژی کنترل دمای هوشمند
- طراحی مؤثر دفع گرما
- حفاظت الکتریکی 6KV
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- رزولوشن 2 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 22 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 150 متر

Specifications

| | | | | | | | |
|-------------------------|--------------------------------------------------------------|------------------|-----------------|-----------------|----------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| sensor | 1/2.8", 2.0 megapixel, progressive scan, CMOS | | | | | Smart Features | Audio detection, Cross line, intrusion, object left, object removed, people counting, face detection, Auto tracking |
| Lens | 5.2 - 114.4mm, AF automatic focusing and motorized zoom lens | | | | | General Function | Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication |
| Digital Zoom | 16 | | | | | Audio Compression | G.711 |
| Optical Zoom | 22 | | | | | Two-way Audio | Supported |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) | Suppression | Supported |
| | 5.2 | 80.7(264.7ft) | 32.3(105.9ft) | 16.1(52.9ft) | 8.1(26.5ft) | Sampling Rate | 8KHZ |
| Angle of View (H) | 114.4 | 1775.2(5824.1ft) | 710.1(2329.6ft) | 355.0(1164.8ft) | 177.5(582.4ft) | Edge Storage | Micro SD, up to 256GB |
| | 53.4° ~ 2.7° | | | | | Network Storage | ANR |
| Angle of View (V) | 32.3° ~ 1.5° | | | | | Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS |
| Angle of View (D) | 60.3° ~ 3.1° | | | | | Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API |
| Shutter | Auto/Manual, shutter time: 1 - 1/100000s | | | | | Pan Range | 360° (endless) |
| Minimum Illumination | Colour: 0.003Lux (F1.5, AGC ON) 0Lux with IR | | | | | Pan Speed | 0.1°/s - 240°/s Preset speed: 300°/s |
| Iris | Auto/Manual; F1.5 - F3.8 | | | | | Tilt Range | -15° - 90° (auto reverse) |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | | Tilt Speed | 0.1° - 80°/s Preset speed: 80°/s |
| Digital noise reduction | 2D/3D DNR | | | | | Number of Presets | 1024 |
| S/N | >52 dB | | | | | Patrol | Preset patrol, route patrol, recorded patrol |
| IR Range | UP to 150m (492ft) | | | | | Home Position | Supported |
| Defog | Digital Defog | | | | | Audio I/O | Audio Cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p] |
| WDR | 120dB | | | | | Alarm I/O | 1/1 |
| Video Compression | Ultra 265, H.265, H.264, MJPEG | | | | | Power | DC 12V±10%, PoE (PSE Required) Power consumption: 4 - 27.6W |
| H.264 code profile | Baseline profile, Main Profile, High Profile | | | | | Dimensions (Ø x H) | Ø220 x 369mm (Ø8.7" x 14.5") |
| Frame Rate | Main Stream: 2MP (1920*1080), Max 60fps; | | | | | Weight | 3.4kg (7.5lb) |
| | Sub Stream: 2MP (1920*1080), Max 60fps; | | | | | Working Environment | -40°C - 65°C (-40°F - 149°F), Humidity: ≤95% RH (non-condensing) |
| | Third Stream: D1 (720*576), Max 60fps | | | | | Ingress Protection | IP66 |
| HLC | Supported | | | | | Reset Button | Supported |
| BLC | Supported | | | | | | |
| EIS | Supported | | | | | | |
| OSD | Up to 8 OSDs | | | | | | |
| Privacy Mask | Up to 24 areas | | | | | | |
| ROI | Up to 8 areas | | | | | | |
| Motion Detection | Up to 4 areas | | | | | | |

Dimensions

