

# IPZ-P6225W-I150S

2MP 25x Lighthunter Network PTZ Dome Camera



Network  
Cameras

NVRs

AHD  
Series

Video  
Decoders

Switches

Accessories

## قابلیت های کلیدی

- زوم اپتیکال تا 25 برابر بزرگ نمایی
- IR هوشمند تا 150 متر
- تعلق ضد بازتاب نور مادون قرمز
- رزولوشن 2 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +65 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP66

## Specifications

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS					Two-way Audio	Support
Minimum Illumination	Colour: 0.001 Lux (F1.5, AGC ON) 0 Lux with IR					Suppression	Support
Day/Night	IR-cut filter with auto switch (ICR)					Sampling Rate	8 kHz
Shutter	Auto, 1 - 1/100000s					Edge Storage	Micro SD, up to 256 GB
WDR	120dB					Network Storage	ANR, NAS(NFS)
S/N	>52dB					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Lens type	5- 125mm, AF automatic focusing and motorized zoom lens					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Optical Zoom	25					User/Host	Up to 32 users. 2 user levels: administrator and common user
Iris	Auto; F1.5 ~ F3.0					Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Angle of View (H)	54.37° ~ 2.68°					Web Browser	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Angle of View (V)	32.23° ~ 1.51°					Pan Range	360° (endless)
Angle of View (D)	66.88° ~ 3.16°					Pan Speed	2°/s ~ 75°/s Preset speed: 80°/s
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Number of Presets	1024
	5	85.3(280.0ft)	34.1(112.0ft)	17.1(56.0ft)	8.5(28.0ft)	Preset Patrol	16 patrols, up to 64 presets for each patrol
IR Range	125	1706.9 (5600.1ft)	682.8(2240.0ft)	341.4(1120.0ft)	170.7(560.0ft)	Route Patrol	16 patrols, up to 32 actions for each patrol
	Up to 150m IR range						Recorded Patrol
Wavelength	850nm					Patrol Stay Time	15s-1800s
IR On/Off Control	Auto/Manual					Home Position	Support
Video Compression	Ultra 265, H.265, H.264, MJPEG					Audio I/O	1/1
Frame Rate	Main Stream: 2MP(1920*1080), Max 30fps;					Alarm I/O	2/1
	Sub Stream: 720P (1280*720), Max 30fps;					Serial Port	1 RS485
	Third Stream: D1 (720*576), Max 30fps;					Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Bit Rate	128 Kbps-16 Mbps					Video Output	N/A
ROI	Up to 8 areas					Power	DC12V±10% , PoE+ (IEEE802.3 at) Power consumption: Max 25W
OSD	Up to 8 OSDs					Power Interface	Ø 5.5mm coaxial power plug
Privacy Mask	24 areas, up to 4 areas per scene					Dimensions (Ø x H)	Ø220 x 370mm (Ø8.7" x 14.6")
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2					Weight	3.3kg(7.26lb)
Digital noise reduction	2D/3D DNR					Working Environment	-40°C-65°C(-40°F ~ 149°F), Humidity: ≤95% RH (non-condensing)
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise					Surge protection	6KV
HLC	Support					Reset button	Support
BLC	Support					Protection	Ingress Protection: IP66 Vandal Resistant: N/A
Defog	Digital Defog						
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication						
Smart Features	Audio detection, Deep Learning, Smart Intrusion Prevention, (Cross Line, Enter Area, Leave Area, Intrusion), People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 8), Auto Tracking						
Audio Compression	G.711U, G.711A						

## Dimensions

