

IPZ-P6233W-S

2MP 33x Starlight Network PTZ Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- تکنولوژی کنترل دمای هوشمند
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- رزولوشن 2 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع

Specifications

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens
Digital Zoom	16
Optical Zoom	33
DORI Distance	Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m)
	4.5 69.8 27.9 14 7 148.5 2094.8 837.9 419 209.5
Angle of View (H)	62.67° ~ 2.82°
Angle of View (V)	38.4° ~ 1.3°
Angle of View (D)	77.1° ~ 3.3°
Shutter	Auto/Manual; shutter time: 1 - 1/100000s
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON)
	B/W: 0.0001Lux(F1.5, AGC ON)
Iris	Auto/Manual; F1.5 ~ F4.0
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>52dB
Defog	Defog Digital
WDR	120dB
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps;
	Sub Stream: 2MP (1920*1080), Max 30fps;
	Third Stream: D1 (720*576), Max 30fps
HLC	Supported
BLC	Supported
EIS	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart Features	Audio detection, Cross line, intrusion, object left, object removed, people counting, face capture, Auto tracking

General Function	6Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	.711
Two-way audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 400°/s
	Preset speed: 400°/s
Tilt Range	1° ~ 90°
Tilt Speed	0.1° ~ 240°/s
	Preset speed: 240°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
Audio I/O	Audio cable
	1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/1
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
Power	AC 24V±25%, DC 24V±25%, PoE (IEEE 802.3at)
	Power consumption: Max 16W
Dimensions (Ø x H)	Ø218 x 298mm (Ø8.6" x 11.7")
Weight	4.2kg (9.3lb)
Working Environment	-30°C ~ 70°C (-31°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported

Dimensions

