

IPZ-P6433W-I150S

4MP 33x Lighthunter Network PTZ Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- رزولوشن 4 مگاپیکسل
- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 150 متر
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 33 برابر بزرگ نمایی

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS				Audio Compression	G.711U,G.711A
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR				Two-way Audio	Support
Day/Night	IR-cut filter with auto switch (ICR)				Suppression	Support
Shutter	Auto/Manual, 1 - 1/100000s				Sampling Rate	8 kHz
WDR	120dB				Edge Storage	Micro SD, up to 256 GB
S/N	>56dB				Network Storage	ANR,NAS(NFS) Network
Lens type	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens				Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS
Digital Zoom	16				Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API,SDK
Optical Zoom	33				User/Host	Up to 32 users. 2 user levels: administrator and common user
Iris	Auto; F1.5 - F4.0				Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Angle of View (H)	53.0° - 2.3°				Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Angle of View (V)	31.0° - 1.3°				Pan Range	360° (endless)
Angle of View (D)	65.2° - 2.7°				Pan Speed	0.1°/s - 200°/s Preset speed: 300°/s
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Tilt Range	-15° - 90° (auto reverse)
					Tilt Speed	0.1°/s - 200°/s Preset speed: 240°/s
IR Range	Up to 150m IR range				Number of Presets	1024
Wavelength	850nm				Preset Patrol	16 patrols, up to 64 presets for each patrol
IR On/Off Control	Auto/Manual				Patrol Stay Time	15s-1800s
Video Compression	Ultra 265, H.265, H.264, MJPEG				Home Position	Support
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps;				Audio I/O	1/1
	Sub Stream: 2MP (1920*1080), Max 30fps;				Alarm I/O	2/1
	Third Stream: D1 (720*576), Max 30fps;				Serial Port	1 RS485
Video Bit Rate	128 Kbps-16 Mbps				Network	1 * RJ45 10M/100M Base-TX Ethernet
ROI	Up to 8 areas				Video Output	1 BNC
OSD	Up to 8 OSDs				Power	AC 24V±25%, DC 24V±25%, PoE+ (IEEE802.3 at) Power consumption: Max 25W
Privacy Mask	24 areas, up to 4 areas per scene				Dimensions (Ø x H)	Ø227 x 384.8mm (Ø8.9" x 15.1")
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				Weight	5.28kg(11.64lb)
Digital noise reduction	2D/3D DNR				Working Environment	-40°C ~70°C (-40°F ~ 158°F) , Humidity: ≤95% RH (non-condensing)
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				Surge protection	6KV
HLC	Support				Reset button	Support
BLC	Support				Protection	Ingress Protection: IP66 Vandal Resistant: N/A
Defog	Digital Defog					
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication					
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking					

Dimensions

